

Quality Assurance
Audit Criteria
This product was designed and manufactured to meet the following specifications:
Performance is confirmed by testing on an audit basis.

USP Oxidizable Substances
Effluent was negative after an RO water flush.

Gravimetric Extractables
The extractables level was equal to or less than 1500mg/m² after an RO water flush.

Quality Assurance Lot
Release Criteria
Every unit is tested by Manufacturing and released by Quality Assurance to the following specifications:

Integrity
Each unit exhibited air flow through fully-wetted membranes less than or equal to 60 cc/min at 10 psig (0.7 bar) inlet pressure.

Pressure Drop
Samples met a maximum pressure drop of less than or equal to 3.5 psi (0.24 bar) at 0.8 gpm (3.0 L/min) average cross flow of clean water.

ISO 9001 Quality Standard
This product was manufactured in a Millipore facility which adheres to Good Manufacturing Practices.
Good Manufacturing Practices
This product was manufactured in a Millipore facility which adheres to Good Manufacturing Practices.

Materials
Membrane: Polyethersulfone
Screens: Polypropylene
Endcap: Polysulfone
Adhesives: Urethane
Toxicity: All parts in fluid paths were tested and meet the criteria of the USP Class VI Biological Tests for Plastics.
ISO 9001 Quality Systems Standard.
This product was manufactured in a Millipore facility which adheres to Good Manufacturing Practices.

100% Integrity Tested in Manufacturing
Each unit must pass the Millipore Integrity Test based on air flow through the fully-wetted membranes of the filter.

Millipore, Durapore and Pellicon are registered trademarks of Millipore Corporation.
ISO is a registered trademark of the International Standards Organization.
00099620PU Rev F 06/08

Pellicon® 2 Filter

Quality Assurance
Audit Criteria
This product was designed and manufactured to meet the following specifications:
Performance is confirmed by testing on an audit basis.

USP Oxidizable Substances
Effluent was negative after an RO water flush.

Gravimetric Extractables
The extractables level was equal to or less than 1500mg/m² after an RO water flush.

Quality Assurance
Audit Criteria
This product was designed and manufactured to meet the following specifications:
Performance is confirmed by testing on an audit basis.

Quality Assurance
Audit Criteria
This product was designed and manufactured to meet the following specifications:
Performance is confirmed by testing on an audit basis.

Quality Assurance
Audit Criteria
This product was designed and manufactured to meet the following specifications:
Performance is confirmed by testing on an audit basis.

Quality Assurance
Audit Criteria
This product was designed and manufactured to meet the following specifications:
Performance is confirmed by testing on an audit basis.

Quality Assurance
Audit Criteria
This product was designed and manufactured to meet the following specifications:
Performance is confirmed by testing on an audit basis.

Quality Assurance
Audit Criteria
This product was designed and manufactured to meet the following specifications:
Performance is confirmed by testing on an audit basis.

Quality Assurance
Audit Criteria
This product was designed and manufactured to meet the following specifications:
Performance is confirmed by testing on an audit basis.

Quality Assurance
Audit Criteria
This product was designed and manufactured to meet the following specifications:
Performance is confirmed by testing on an audit basis.

Quality Assurance
Audit Criteria
This product was designed and manufactured to meet the following specifications:
Performance is confirmed by testing on an audit basis.

Quality Assurance
Audit Criteria
This product was designed and manufactured to meet the following specifications:
Performance is confirmed by testing on an audit basis.

Quality Assurance
Audit Criteria
This product was designed and manufactured to meet the following specifications:
Performance is confirmed by testing on an audit basis.

Quality Assurance
Audit Criteria
This product was designed and manufactured to meet the following specifications:
Performance is confirmed by testing on an audit basis.

Quality Assurance
Audit Criteria
This product was designed and manufactured to meet the following specifications:
Performance is confirmed by testing on an audit basis.

Quality Assurance
Audit Criteria
This product was designed and manufactured to meet the following specifications:
Performance is confirmed by testing on an audit basis.

Quality Assurance
Audit Criteria
This product was designed and manufactured to meet the following specifications:
Performance is confirmed by testing on an audit basis.

Quality Assurance
Audit Criteria
This product was designed and manufactured to meet the following specifications:
Performance is confirmed by testing on an audit basis.

Quality Assurance
Audit Criteria
This product was designed and manufactured to meet the following specifications:
Performance is confirmed by testing on an audit basis.

Quality Assurance
Audit Criteria
This product was designed and manufactured to meet the following specifications:
Performance is confirmed by testing on an audit basis.

Quality Assurance
Audit Criteria
This product was designed and manufactured to meet the following specifications:
Performance is confirmed by testing on an audit basis.

Quality Assurance
Audit Criteria
This product was designed and manufactured to meet the following specifications:
Performance is confirmed by testing on an audit basis.

Quality Assurance
Audit Criteria
This product was designed and manufactured to meet the following specifications:
Performance is confirmed by testing on an audit basis.